



Glorit (AT)

Concealed connecting systems for decks, boards and wall panels indoors as well as outdoors

- Do you value a great looking deck surface? Then use the non-visible connecting system from KNAPP® Connectors.
- Demanding customers desire alternatives to traditional standard decking.
- KNAPP® offers systems for immaculate decking, boat piers and wall panels.

- Do you value an attractive surface? For this reason, you should use a concealed connecting system for your timber deck.
- Demanding clients desire alternatives to conventional, standard decks.
- KNAPP® offers you systems for optically-flawless decks, boat docks and wall panels.



Kulmer (AT)



Escabelle (FR)



Glorit (AT)



QUATRO 65



Z-DECK



Eb-Ty® LC



Country house "Am Dünenweg" | Wilkening (D)
© www.weidner-bfwwf.de

QUATRO 65

The deck board and panel connector

Recommended for spacing no smaller than 7 mm




Quatro 65/25
Art.-No. Ko81

Quatro 65/30
Art.-No. Ko80

- Concealed from the first board to the last
- Constructive wood protection against moisture
- Optimal rear ventilation through spacing between the boards and the joists
- Also for timber façades and formwork for which rear ventilation has been implemented
- Easy installation with mounting templates
- Connection allows expansion and contraction
- UV and weather-resistant plastic

www.knapp-connectors.com/quatro65



Quantités nécessaires		
Dielenbreite	Verbinder / m ²	m ² / Verpackungseinheit
150 mm	approx. 17 pairs	6 m ²
100 mm	approx. 25 pairs	4 m ²
(For joist spacing of 500 mm)		

Tips:

- Even the best connecting system cannot offset the poor quality of some timber. Please ensure that the timber is dry and in particular avoid timber from the core and spiral-grained boards.
- Recommended length of the boards: maximum 3 m.
- Pre-drill, particularly with hardwoods, such as oak.
- Follow the installation instructions of your quality timber supplier.

QUATRO 65 Installation

- Pre-drilling and continuous positioning of the joint spacing with the mounting template



Pre-drill with the template



Fasten to the boards with screws



Fasten to the joists with screws



QUATRO 65 as a spacer



Mount the final board



Up-to-date prospectuses and catalogues as well as the price lists can be downloaded as a pdf from our website at www.knapp-connectors.com/downloads



Glorit (AT)

Z-DECK

Mount deck boards perfectly

- Recommended for warped boards and spacing starting at 7 mm

Z-Deck
Art.-No. Ko82



Stainless steel CS-screws
A2 4.5x35 mm with cut-point



- Robust – even for beach and boat docks
- Boards can be quickly and individually replaced
- Optimal wood protection through self-cleaning joint design
- More solid than visible screw connections from the top
- Increased security against twisting of the boards
- Connectors and screws are made of stainless steel

Quantités nécessaires		
Largeur de lame	Nb de fixation / m ²	Nb de m ² / conditionnement
150 mm	approx. 28 piece	9 m ²
100 mm	approx. 40 piece	6 m ²
(For joist spacing of 500 mm)		

Tips:

- Even the best connecting system cannot offset the poor quality of some timber. Please ensure that the timber is dry and in particular avoid timber from the core and spiral-grained boards.
- Pre-drill, particularly with hardwoods, such as oak.
- Follow the installation instructions of your quality timber supplier.

www.knapp-connectors.com/z-deck

Z-DECK Installation

- Create the groove with the mortise profile router



Routing with the router
(optional)



Drive in



Screw in



The Z-DECK is completely mounted



Eb-Ty® LC

Simple for perfect spacing

■ For 6.5 mm of spacing



Eb-Ty® Art.-No. Z401

Stainless steel CS-screws
A2 4.5x55 mm with cut-point

- Concealed mounting
- Quick and easy mounting
- Integrated spacer guarantees even spacing
- UV and weather-resistant plastic



Quantités nécessaires

Largeur de lame	Nb de fixation / m²	Nb de m² / conditionnement
150 mm	env. 15 pièces	16 m²
100 mm	env. 23 pièces	10 m²
(Pour un entre-axe de lambourde de 500 mm)		

Tips:

- Even the best connecting system cannot offset the poor quality of some timber. Please ensure that the timber is dry and in particular avoid timber from the core and spiral-grained boards.
- Recommended length of the boards: maximum 3 m.
- Pre-drill, particularly with hardwoods, such as oak.
- Follow the installation instructions of your quality timber supplier.

www.knapp-connectors.com/eb-ty

Eb-Ty® LC installation

Precisely set the depth to "20" with the lamella machine and the groove depth T using the fine adjustment.




Routing



Fastening with screws



Add the next boardsuivante



Escabelle(F)

New website –
new Newsletter

▶▶▶ Sign up now!

Knapp GmbH | Wassergasse 31 | A-3324 Euratsfeld | Tel.: +43 (0)7474 / 799 10
Fax: +43 (0)7474 / 799 10 99 | E-Mail: info@knapp-connectors.com